



MARDERfix BATTERY

Marten-free in the car, house and yard thanks to acoustic signal

Batteries (alkaline)	4x 1.5 Volt (Baby/C/R14)
Operating time	approx. 1 year
Frequency range	12 kHz +/- 10%
Sound pressure	approx. 75 dB
Beam angle	approx. 140°
Sufficient up to	40 m ²
Guarantee	2 years
Article no.	06580
Product Length in mm	140
Product width in mm	80
Product height in mm	30
Weight pcs. incl. Verp. in g	172



Marten-free in the car, house and yard thanks to acoustic signal.

The marten repellent device produces a very high sine tone of approx. 12 kHz, almost inaudible to humans. The marten finds this frequency extremely unpleasant. He will avoid this area. For use in dry rooms or weather-protected areas such as carports, attics and cellars. Also offers protection from rodents.

Application

Before using any marten repellent measure, the marten's scent mark must be removed. MARDERfix pre-cleaner is recommended for this purpose. The sine tone works like the beam of a flashlight and does not penetrate matter. The sound should be able to propagate as unhindered as possible. Position the device accordingly.

01 Pre-treatment with pre-cleaner

Spray the cooled engine compartment and wheel arches generously with the foam from the marten pre-cleaner (point of attack for other martens). After a short exposure time, rinse off the foam thoroughly – for example with a watering can. The vehicle is therefore neutral.

02 Installation acoustic device

Position and secure the housing (e.g. with cable ties) so that the sound can spread as freely as possible. The sine tone works like the beam of a flashlight and does not penetrate matter. Switch on the appliance (green "On/Off button"). Control function light is active.

Note

Do not install near hot or moving parts! Always read the label and product information before use.